

Technical Data Sheet

Product

OB41 6-in-1 Multi-Oil Spray is a specially formulated light viscosity lubricating fluid with excellent penetrating and de-watering properties. For use in water repellent applications as found on Truck, Bus, Car and Motorcycle Ignitions. Containing special corrosion inhibitors and displacement additive components, it will quickly penetrate and lubricate threads, displacing water and depositing a high grade moisture barrier giving protection and sealing capabilities for longer periods.

Applications

Safe to use on electrical components such as Starters, Alternators, Electric Motors, Switch Gear and High and Low Tension Cable and Wiring. Can be used anywhere where water, condensation or steam create a hazard. As a rust preventative, **OB41 6-in-1 Multi-Oil Spray** can be used to remove machining swarf water and produce short to medium term protection when parts are stored indoors. Ideal for prevention of corrosion on steel, brass, copper and aluminium.

Important

Always read the Safety Data Sheet before use.

Storage

Store in a cool dry well ventilated area at between 10-30°C

Shelf Life

36 months from date of manufacture.

Typical Characters

Physical appearance	Light straw colour
Odour	Oily
Relative Density	0.808
Autoflammability	>250°C

Protection

Vehicle ignition & wiring systems	Medium to long term
Rust prevention - indoors	Medium term
Rust prevention - outdoors	Short term

Manufacturing Standard

ISO 9001:2015



Disclaimer

The Information provided herein, especially recommendations for the usage and the application of this products, is provided in good faith, and no liability on the part of Siroflex Ltd is stated or implied. No employee of Siroflex Ltd has the authority to waive or alter in any way the content of this document. Due to different materials used, as well as to varying working conditions, production techniques, and the requirements of the end users, all of which are beyond our control, we strongly recommend that thorough and extensive trials are carried out in order to test the suitability of our products with regard to the required processes and applications. This should also include an ageing test which should be applied to all substrates used. It is also the responsibility of the purchaser and end user of this product to ensure that all appropriate actions necessary for the protection of the environment, and for the health and safety of their employees are observed. This datasheet replaces all former versions