

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product Name 2%+HDW3URWHFW)LUH5HVLVWDQW+IEULGPO:KLWH
Pure substance/mixture Mixture

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended use Sealant
Uses advised against None known

1.3. Details of the supplier of the safety data sheet

Company Name

Siroflex Limited
Dodworth Business Park
Dodworth, Barnsley
South Yorkshire, S75 3SP
Tel +44 (0)1226 771600 Fax +44 (0)1226 771601
Further information available from: www.ob1original.com

(P H U J H Q F \ W H O H S K R Q H Q X P E H U

United Kingdom + 44 (0) 1226 771600 (Office Hours Only)
Ireland NPIC - National Poison Information Centre
Members of the Public: +353 (0) 1 8092166 (8.00 am to 10.00 pm - 7 days a week)
Healthcare Professionals: +353 (0)1 8092566 (24 hour service)
112

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No 1272/2008

Skin sensitisation	Category 1A - (H317)
Chronic aquatic toxicity	Category 3 - (H412)

2.2. Label elements

Contains Reaction mass of Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate & N-[3-(Dimethoxymethylsilyl)propyl]-ethylenediamine & Trimethoxyvinylsilane & N-(3-(trimethoxysilyl)propyl)ethylenediamine & Dioctyltinbis(acetylacetonate)



SAFETY DATA SHEET

OB1 HeatProtect Fire Resistant Hybrid 290ml White
Date 18.10.2024

Replaces: N/A
Ref:0641.0.BB/DL

Signal word

Warning

Hazard statements

H317 - May cause an allergic skin reaction.
H412 - Harmful to aquatic life with long lasting effects.

EU Specific Hazard Statements

EUH212 - Warning! Hazardous respirable dust may be formed when used. Do not breathe dust

Precautionary Statements - EU (§28, 1272/2008)

P101 - If medical advice is needed, have product container or label at hand
P102 - Keep out of reach of children
P261 - Avoid breathing dust/fume/gas/mist/vapours/spray
P280 - Wear protective gloves
P302 + P352 - IF ON SKIN: Wash with plenty of water and soap
P501 - Dispose of contents/ container to an approved waste disposal plant

2.3. Other hazards

Small amounts of methanol (CAS 67-56-1) are formed by hydrolysis and released upon curing. Harmful to aquatic life.

PBT & vPvB

This mixture contains no substance considered to be persistent, bioaccumulating or toxic (PBT). This mixture contains no substance considered to be very persistent nor very bioaccumulating (vPvB).

SECTION 3: Composition/information on ingredients

3.1 Substances

Not applicable

3.2 Mixtures

Chemical name	EC No	CAS No	Weight-%	Classification according to Regulation (EC) No. 1272/2008 [CLP]	Specific concentration limit (SCL)	REACH registration number
Titanium dioxide	236-675-5	13463-67-7	1 - <5	^	-	01-2119489379-17-XXXX
Trimethoxyvinylsilane	220-449-8	2768-02-7	1- <2.5	Skin Sens. 1B (H317) Acute Tox. 4 (H332) Flam. Liq. 3 (H226)	-	01-2119513215-52-XXXX
Diocetyl tinbis(acetylacetonate)	483-270-6	54068-28-9	0.1 - <1	STOT SE 2 (H371) Skin Sens. 1 (H317)	Skin Sens. 1 :: C>=5%	01-0000020199-67-XXXX
N-(3-(trimethoxysilyl)propyl)ethylenediamine	217-164-6	1760-24-3	0.1 - <1	Eye Dam. 1 (H318) Skin Sens. 1 (H317) Acute Tox. 4 (H332) STOT SE 3 (H335)	-	01-2119970215-39-XXXX

SAFETY DATA SHEET

OB1 HeatProtect Fire Resistant Hybrid 290ml White
Date 18.10.2024

Replaces: N/A
Ref:0641.0.BB/DL

Reaction mass of Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate	915-687-0	1065336-91-5	0.1 - <1	Skin Sens. 1A (H317) Repr. 2 (H361f) Aquatic Acute 1 (H400) Aquatic Chronic 1 (H410)	-	01-2119491304-40-XXXX
N-[3-(Dimethoxymethylsilyl)propyl]-ethylenediamine	221-336-6	3069-29-2	0.1 - <1	Acute Tox. 4 (H302) Skin Irrit. 2 (H315) Eye Dam. 1 (H318) Skin Sens. 1A (H317)	-	01-2119963926-21-xxxx

NOTE [5] - This substance is exempted from registration according to the provisions of Article 2(7)(a) and Annex V of REACH

Full text of H- and EUH-phrases: see section 16

Note: ^ indicates not classified, however, the substance is listed in section 3 as it has an OEL

This product does not contain candidate substances of very high concern at a concentration $\geq 0.1\%$ (Regulation (EC) No. 1907/2006 (REACH), Article 59)

SECTION 4: First aid measures

4.1. Description of first aid measures

General advice	Show this safety data sheet to the doctor in attendance. If medical advice is needed, have product container or label at hand.
Inhalation	Remove to fresh air. If symptoms persist, call a doctor.
Eye contact	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
Skin contact	Wash with soap and water. May cause an allergic skin reaction. In the case of skin irritation or allergic reactions see a doctor.
Ingestion	Call a doctor immediately. Rinse mouth thoroughly with water. Never give anything by mouth to an unconscious person. Small amounts of toxic methanol are released by hydrolysis.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms None known.

4.3. Indication of any immediate medical attention and special treatment needed

Note to doctors Treat symptomatically. Small amounts of methanol (CAS 67-56-1) are formed by hydrolysis and released upon curing.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable Extinguishing Media	Water spray, carbon dioxide (CO ₂), dry chemical, alcohol-resistant foam.
Unsuitable extinguishing media	Full water jet.

SAFETY DATA SHEET

OB1 HeatProtect Fire Resistant Hybrid 290ml White
Date 18.10.2024

Replaces: N/A
Ref:0641.0.BB/DL

5.2. Special hazards arising from the substance or mixture

Specific hazards arising from the chemical Thermal decomposition can lead to release of irritating gases and vapours.

Hazardous combustion products Carbon oxides. Carbon monoxide. Carbon dioxide (CO₂). Nitrogen oxides (NO_x). Silicon dioxide.

5.3. Advice for firefighters

Special protective equipment and precautions for fire-fighters Wear self contained breathing apparatus for fire fighting if necessary.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions Use personal protective equipment as required. Ensure adequate ventilation. Do not get in eyes, on skin, or on clothing.

For emergency responders Use personal protection recommended in Section 8.

6.2. Environmental precautions

Environmental precautions Prevent product from entering drains. Do not allow to enter into soil/subsoil. See Section 12 for additional Ecological Information.

6.3. Methods and material for containment and cleaning up

Methods for containment Prevent further leakage or spillage if safe to do so.

Methods for cleaning up Take up mechanically, placing in appropriate containers for disposal.

Prevention of secondary hazards Clean contaminated objects and areas thoroughly observing environmental regulations.

6.4. Reference to other sections

Reference to other sections See section 8 for more information. See section 13 for more information.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling Handle in accordance with good industrial hygiene and safety practice. Avoid contact with skin, eyes or clothing. Ensure adequate ventilation. In case of insufficient ventilation, wear suitable respiratory equipment. Do not eat, drink or smoke when using this product. Take off contaminated clothing and wash it before reuse.

General hygiene considerations Do not eat, drink or smoke when using this product. Wash hands before breaks and after work.

7.2. Conditions for safe storage, including any incompatibilities

Storage Conditions Protect from moisture. Keep away from food, drink and animal feedingstuffs.

Recommended storage temperature Keep at temperatures between 10 and 35 °C.

7.3. Specific end use(s)

Specific use(s)
Sealant.

SAFETY DATA SHEET

OB1 HeatProtect Fire Resistant Hybrid 290ml White
Date 18.10.2024

Replaces: N/A
Ref:0641.0.BB/DL

Risk Management Methods (RMM) The information required is contained in this Safety Data Sheet.

Other information Observe technical data sheet.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure Limits Small amounts of methanol (CAS 67-56-1) are formed by hydrolysis and released upon curing This product contains titanium dioxide in a non-respirable form. Inhalation of titanium dioxide is unlikely to occur from exposure to this product

Chemical name	European Union	United Kingdom
Limestone 1317-65-3	-	TWA: 10 mg/m ³ TWA: 4 mg/m ³ STEL: 30 mg/m ³ STEL: 12 mg/m ³
Titanium dioxide 13463-67-7	-	TWA: 10 mg/m ³ TWA: 4 mg/m ³ STEL: 30 mg/m ³ STEL: 12 mg/m ³
Methyl alcohol 67-56-1	TWA: 200 ppm TWA: 260 mg/m ³ *	TWA: 200 ppm TWA: 266 mg/m ³ STEL: 250 ppm STEL: 333 mg/m ³ Sk*
Diocetylbinbis(acetylacetonate) 54068-28-9	-	TWA: 0.1 mg/m ³ STEL: 0.2 mg/m ³ Sk*

Chemical name	European Union	Ireland	United Kingdom
Methyl alcohol 67-56-1	-	15 mg/L (urine - Methanol end of shift)	-

Derived No Effect Level (DNEL) No information available

Derived No Effect Level (DNEL)

Titanium dioxide (13463-67-7)

Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
worker Long term Local health effects	Inhalation	10 mg/m ³	

Trimethoxyvinylsilane (2768-02-7)

Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
worker Systemic health effects Long term	Inhalation	27,6 mg/m ³	
worker Systemic health effects Long term	Dermal	3,9 mg/kg bw/d	

Diocetylbinbis(acetylacetonate) (54068-28-9)

Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
Long term Systemic health effects worker	Dermal	0.07 mg/kg bw/d	
Long term Systemic health effects	Inhalation	84 mg/m ³	

SAFETY DATA SHEET

OB1 HeatProtect Fire Resistant Hybrid 290ml White
Date 18.10.2024

Replaces: N/A
Ref:0641.0.BB/DL

worker			
Short term Systemic health effects worker	Inhalation	84 mg/m ³	
Long term Short term Local health effects worker	Inhalation	0.091 mg/m ³	

N-(3-(trimethoxysilyl)propyl)ethylenediamine (1760-24-3)

Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
worker Systemic health effects Long term	Inhalation	35.5 mg/m ³	
worker Systemic health effects Long term	Dermal	5 mg/kg bw/d	

Reaction mass of Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate (1065336-91-5)

N-[3-(Dimethoxymethylsilyl)propyl]-ethylenediamine (3069-29-2)

Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
worker Long term Systemic health effects	Inhalation	12 mg/m ³	
worker Long term Systemic health effects	Dermal	1.7 mg/kg bw/d	

Derived No Effect Level (DNEL)

Titanium dioxide (13463-67-7)

Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
Consumer Long term Systemic health effects	Oral	700 mg/kg bw/d	

Trimethoxyvinylsilane (2768-02-7)

Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
Consumer Systemic health effects Long term	Inhalation	18,9 mg/m ³	
Consumer Systemic health effects Long term	Dermal	7,8 mg/kg bw/d	
Consumer Systemic health effects Long term	Oral	0,3 mg/kg bw/d	

N-(3-(trimethoxysilyl)propyl)ethylenediamine (1760-24-3)

Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
Consumer Systemic health effects Long term	Oral	2.5 mg/kg bw/d	
Consumer Systemic health effects	Inhalation	8.7 mg/m ³	

SAFETY DATA SHEET

OB1 HeatProtect Fire Resistant Hybrid 290ml White
Date 18.10.2024

Replaces: N/A
Ref:0641.0.BB/DL

Long term			
Consumer Systemic health effects Long term	Dermal	2.5 mg/kg bw/d	

N-[3-(Dimethoxymethylsilyl)propyl]-ethylenediamine (3069-29-2)			
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
Consumer Long term Systemic health effects	Inhalation	2.9 mg/m ³	
Consumer Long term Systemic health effects	Dermal	0.83 mg/kg bw/d	
Consumer Long term Systemic health effects	Oral	0.83 mg/kg bw/d	

Predicted No Effect Concentration (PNEC) No information available.

Predicted No Effect Concentration (PNEC)	
Titanium dioxide (13463-67-7)	
Environmental compartment	Predicted No Effect Concentration (PNEC)
Marine water	0.0184 mg/l
Freshwater sediment	1000 mg/kg
Freshwater	0.184 mg/l
Marine sediment	100 mg/kg
Soil	100 mg/kg
Microorganisms in sewage treatment	100 mg/l
Freshwater - intermittent	0.193 mg/l

Trimethoxyvinylsilane (2768-02-7)	
Environmental compartment	Predicted No Effect Concentration (PNEC)
Freshwater	0.34 mg/l
Marine water	0.034 mg/l
Microorganisms in sewage treatment	110 mg/l

Diocetylbinbis(acetylacetonate) (54068-28-9)	
Environmental compartment	Predicted No Effect Concentration (PNEC)
Freshwater	26 µg/l
Marine water	2.6 µg/l
Freshwater - intermittent	260 µg/l
Sewage treatment plant	1 mg/l
Freshwater sediment	0.155 mg/kg dry weight
Marine sediment	0.0155 mg/kg dry weight
Soil	0.0158 mg/kg dry weight

N-(3-(trimethoxysilyl)propyl)ethylenediamine (1760-24-3)	
Environmental compartment	Predicted No Effect Concentration (PNEC)
Freshwater	0.062 mg/l
Marine water	0.0062 mg/l
Sewage treatment plant	25 mg/l

N-[3-(Dimethoxymethylsilyl)propyl]-ethylenediamine (3069-29-2)	
Environmental compartment	Predicted No Effect Concentration (PNEC)
Freshwater	0.062 mg/l
Marine water	0.006 mg/l
Sewage treatment plant	25 mg/l
Freshwater sediment	0.24 mg/kg dry weight
Marine sediment	0.024 mg/kg dry weight
Soil	0.01 mg/kg dry weight

SAFETY DATA SHEET

OB1 HeatProtect Fire Resistant Hybrid 290ml White
Date 18.10.2024

Replaces: N/A
Ref:0641.0.BB/DL

8.2. Exposure controls

Engineering controls	Ensure adequate ventilation, especially in confined areas.
Personal protective equipment	
Eye/face protection	Wear safety glasses with side shields (or goggles). Eye protection must conform to standard EN 166.
Hand protection	Wear suitable gloves. Recommended Use: Neoprene™. Nitrile rubber. Butyl rubber. Glove thickness > 0.7mm. The breakthrough time for the mentioned glove material is in general greater than 480 min. Ensure that the breakthrough time of the glove material is not exceeded. Refer to glove supplier for information on breakthrough time for specific gloves. Gloves must conform to standard EN 374
Skin and body protection	None under normal use conditions.
Respiratory protection	In case of inadequate ventilation wear respiratory protection. Wear a respirator conforming to EN 140 with Type A/P2 filter or better. Ensure adequate ventilation, especially in confined areas.
Recommended filter type:	Organic gases and vapours filter conforming to EN 14387. White. Brown.
Environmental exposure controls	Do not allow uncontrolled discharge of product into the environment.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	Solid
Appearance	Paste
Colour	See section 1 for more information
Odour	Characteristic.
Odour threshold	No information available

<u>Property</u>	<u>Values</u>	<u>Remarks • Method</u>
Melting point / freezing point	No data available	None known
Initial boiling point and boiling range	No data available	None known
Flammability	No data available	None known
Flammability Limit in Air		None known
Upper flammability or explosive limits	No data available	
Lower flammability or explosive limits	No data available	
Flash point	> 60 °C	
Autoignition temperature	No data available	None known
Decomposition temperature		None known
pH	.	
pH (as aqueous solution)	No data available	None known
Kinematic viscosity	> 21 mm ² /s	
Dynamic viscosity	No data available	
		Water solubility No data available Product cures with moisture
None known		Solubility(ies) No data available
None known		Partition coefficient No data available
None known		Vapour pressure No data available
None known		Relative density No data available
		Bulk Density No data available
		Liquid Density 1.48
		Relative vapour density No data available
		Particle characteristics
		Particle Size No information available
		Particle Size Distribution No information available

SAFETY DATA SHEET

OB1 HeatProtect Fire Resistant Hybrid 290ml White
Date 18.10.2024

Replaces: N/A
Ref:0641.0.BB/DL

9.2. Other information

VOC Content (%)

9.2.1. Information with regards to physical hazard classes
Not applicable

9.2.2. Other safety characteristics
No information available

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity Product cures with moisture.

10.2. Chemical stability

Stability Stable under normal conditions.

Explosion data

Sensitivity to mechanical impact None.

Sensitivity to static discharge None.

10.3. Possibility of hazardous reactions

Possibility of hazardous reactions None under normal processing.

10.4. Conditions to avoid

Conditions to avoid Product cures with moisture. Protect from moisture. Exposure to air or moisture over prolonged periods. Do not freeze. Keep away from open flames, hot surfaces and sources of ignition.

10.5. Incompatible materials

Incompatible materials None known based on information supplied.

10.6. Hazardous decomposition products

Hazardous decomposition products Small amounts of methanol (CAS 67-56-1) are formed by hydrolysis and released upon curing.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Information on likely routes of exposure

Product Information

Inhalation Based on available data, the classification criteria are not met.

Eye contact Based on available data, the classification criteria are not met.

Skin contact May cause sensitisation by skin contact. Specific test data for the substance or mixture is not available. Repeated or prolonged skin contact may cause allergic reactions with susceptible persons. (based on components).

Ingestion Based on available data, the classification criteria are not met.

SAFETY DATA SHEET

OB1 HeatProtect Fire Resistant Hybrid 290ml White
Date 18.10.2024

Replaces: N/A
Ref:0641.0.BB/DL

Symptoms related to the physical, chemical and toxicological characteristics

Symptoms Itching. Rashes. Hives.

Acute toxicity

Numerical measures of toxicity

The following values are calculated based on chapter 3.1 of the GHS document

ATEmix (inhalation-vapour) 887.70 mg/l

Component Information

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Titanium dioxide	>10000 mg/kg (Rattus)	LD50 > 5000 mg/Kg	= 5.09 mg/L (Rattus) 4 h
Trimethoxyvinylsilane	LD50 = 7120 -7236 mg/kg (Rattus) OECD 401	= 3540 mg/kg (Oryctolagus cuniculus)	LC50 (4hr) 16.8 mg/l (Rattus) OECD TG 403
Diocetylbinbis(acetylacetonate)	LD50 =2500 mg/kg (Rattus)	LD50 >2000 mg/kg (Rattus)	= 5.1 mg/L (Rat) 4 h
N-(3-(trimethoxysilyl)propyl)ethylenediamine	=2295 mg/kg (Rattus)	>2000 mg/Kg (Rattus)	LC50 4H (Aerosol)1.5 - 2.44 mg/L air
Reaction mass of Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate	LD50 = 3230 mg/Kg (Rat) OECD 401	LD50 >3170 mg/Kg (Rat)	-
N-[3-(Dimethoxymethylsilyl)propyl]-ethylenediamine	=200 - 2000 mg/Kg (Rattus) (OECD 401)	>5000 mg/Kg (Oryctolagus cuniculus) (OECD 402)	> 5.2 mg/L (Rat) 4 h

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritation Based on available data, the classification criteria are not met.

Trimethoxyvinylsilane (2768-02-7)

Method	Species	Exposure route	Effective dose	Exposure time	Results
	Rabbit	Dermal	0.5 mL	24 hours	Non-irritant

N-[3-(Dimethoxymethylsilyl)propyl]-ethylenediamine (3069-29-2)

Method	Species	Exposure route	Effective dose	Exposure time	Results
OECD Test No. 404: Acute Dermal Irritation/Corrosion	Rabbit	Dermal			irritant

Serious eye damage/eye irritation Based on available data, the classification criteria are not met.

Trimethoxyvinylsilane (2768-02-7)

Method	Species	Exposure route	Effective dose	Exposure time	Results
OECD Test No. 405: Acute Eye Irritation/Corrosion	Rabbit	eye		24 hours	Non-irritant

N-[3-(Dimethoxymethylsilyl)propyl]-ethylenediamine (3069-29-2)

Method	Species	Exposure route	Effective dose	Exposure time	Results
OECD Test No. 405: Acute Eye Irritation/Corrosion	Rabbit				Eye Damage

SAFETY DATA SHEET

OB1 HeatProtect Fire Resistant Hybrid 290ml White
Date 18.10.2024

Replaces: N/A
Ref:0641.0.BB/DL

Respiratory or skin sensitisation May cause sensitisation by skin contact.

Titanium dioxide (13463-67-7)
Trimethoxyvinylsilane (2768-02-7)

Method	Species	Exposure route	Results
OECD Test No. 406: Skin Sensitisation, Buehler test	Guinea pig	Dermal	sensitising

Diocetyltnbis(acetylacetonate) (54068-28-9)

Method	Species	Exposure route	Results
OECD Test No. 429: Skin Sensitisation: Local Lymph Node Assay		Dermal	> 5 % sensitising

N-[3-(Dimethoxymethylsilyl)propyl]-ethylenediamine (3069-29-2)

Method	Species	Exposure route	Results
OECD Test No. 406: Skin Sensitisation	Guinea pig		Sensitizing

Germ cell mutagenicity Based on available data, the classification criteria are not met.

Component Information
Trimethoxyvinylsilane (2768-02-7)

Method	Species	Results
OECD Test No. 471: Bacterial Reverse Mutation Test	in vitro	Not mutagenic

Carcinogenicity Based on available data, the classification criteria are not met.

Reproductive toxicity Based on available data, the classification criteria are not met.

Trimethoxyvinylsilane (2768-02-7)

Method	Species	Results
OECD Test No. 422: Combined Repeated Dose Toxicity Study with the Reproduction/Developmental Toxicity Screening Test	Rat	Not Classifiable

STOT - single exposure Based on available data, the classification criteria are not met.

STOT - repeated exposure Based on available data, the classification criteria are not met.

Trimethoxyvinylsilane (2768-02-7)

Method	Species	Exposure route	Effective dose	Exposure time	Results
OECD Test No. 413: Sub-chronic Inhalation Toxicity: 90-day Study	Rat	Inhalation vapour		90 days	0.058 NOAEL

Aspiration hazard Based on available data, the classification criteria are not met.

11.2. Information on other hazards

SAFETY DATA SHEET

OB1 HeatProtect Fire Resistant Hybrid 290ml White
Date 18.10.2024

Replaces: N/A
Ref:0641.0.BB/DL

11.2.1. Endocrine disrupting properties

Endocrine disrupting properties No information available.

11.2.2. Other information

Other adverse effects No information available.

SECTION 12: Ecological information

12.1. Toxicity

Ecotoxicity Harmful to aquatic life with long lasting effects.

Chemical name	Algae/aquatic plants	Fish	Toxicity to microorganisms	Crustacea	M-Factor	M-Factor (long-term)
Titanium dioxide 13463-67-7	LC50 (96h) >10000 mg/l (Cyprinodon variegatus) OECD 203	-	-	-		
Trimethoxyvinylsilane 2768-02-7	EC 50 (72h) > 957 mg/l (Desmodesmus subspicatus) EU Method C.3	LC50 (96h) = 191 mg/l (Oncorhynchus mykiss)	-	EC50(48hr) 168.7mg/l (Daphnia magna)		
Diocetyl tinbis(acetylacetonate) 54068-28-9	-	LC50 (96h) =86 mg/L (Static)	-	EC50 (48h) =58.6 mg/L (Daphnia magna)		
N-(3-(trimethoxysilyl)propyl)ethylenediamine 1760-24-3	-	LC50 (96H) =597 mg/L (Danio rerio)Semi-static	-	EC50 (48h) =81mg/L Daphnia magna Static		
Reaction mass of Bis(1,2,2,6,6-pentamethyl-4-piperidyl)sebacate and Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate 1065336-91-5	EC50 (72 h) 1,68 mg/l (growth rate), Desmodesmus subspicatus (OECD 201)	LC50 (96 h) 0,9 mg/l, Brachydanio rerio (OECD 203)	-	-	1	1

12.2. Persistence and degradability

Persistence and degradability No information available.

Trimethoxyvinylsilane (2768-02-7)

Method	Exposure time	Value	Results
OECD Test No. 301F: Ready Biodegradability: Manometric Respirometry Test (TG 301 F)	28 days	BOD	51 % Not readily biodegradable

12.3. Bioaccumulative potential

Bioaccumulation

Component Information

Chemical name	Partition coefficient
Trimethoxyvinylsilane	1.1
N-(3-(trimethoxysilyl)propyl)ethylenediamine	-0.3
Reaction mass of Bis(1,2,2,6,6-pentamethyl-4-piperidyl)sebacate and Methyl 1,2,2,6,6-pentamethyl-4-piperidyl	2.77

SAFETY DATA SHEET

OB1 HeatProtect Fire Resistant Hybrid 290ml White
Date 18.10.2024

Replaces: N/A
Ref:0641.0.BB/DL

sebacate

12.4. Mobility in soil

Mobility in soil No information available.

12.5. Results of PBT and vPvB assessment

PBT and vPvB assessment

Chemical name	PBT and vPvB assessment
Titanium dioxide	The substance is not PBT / vPvB PBT assessment does not apply
Trimethoxyvinylsilane	The substance is not PBT / vPvB
Dioctyltinbis(acetylacetonate)	The substance is not PBT / vPvB
N-(3-(trimethoxysilyl)propyl)ethylenediamine	The substance is not PBT / vPvB
Reaction mass of Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate	The substance is not PBT / vPvB
N-[3-(Dimethoxymethylsilyl)propyl]-ethylenediamine	The substance is not PBT / vPvB

12.6. Endocrine disrupting properties

Endocrine disrupting properties No information available.

12.7. Other adverse effects

No information available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste from residues/unused products	Dispose of contents/container in accordance with local, regional, national, and international regulations as applicable.
Contaminated packaging	Handle contaminated packages in the same way as the product itself.
European Waste Catalogue	08 04 09* waste adhesives and sealants containing organic solvents or other dangerous substances
Other information	Waste codes should be assigned by the user based on the application for which the product was used.

SECTION 14: Transport information

Land transport (ADR/RID)

14.1 UN number or ID number	Not regulated
14.2 Proper Shipping Name	Not regulated
14.3 Transport hazard class(es)	Not regulated
14.4 Packing group	Not regulated
14.5 Environmental hazards	Not applicable
14.6 Special Provisions	None

IMDG

14.1 UN number or ID number	Not regulated
14.2 Proper Shipping Name	Not regulated
14.3 Transport hazard class(es)	Not regulated
14.4 Packing group	Not regulated
14.5 Marine pollutant	NP

SAFETY DATA SHEET

OB1 HeatProtect Fire Resistant Hybrid 290ml White
Date 18.10.2024

Replaces: N/A
Ref:0641.0.BB/DL

14.6 Special Provisions None
14.7 Maritime transport in bulk according to IMO instruments Not applicable

Air transport (ICAO-TI / IATA-DGR)

14.1 UN number or ID number Not regulated
14.2 Proper Shipping Name Not regulated
14.3 Transport hazard class(es) Not regulated
14.4 Packing group Not regulated
14.5 Environmental hazards Not applicable
14.6 Special Provisions None

Section 15: REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

European Union

Take note of Directive 98/24/EC on the protection of the health and safety of workers from the risks related to chemical agents at work

Check whether measures in accordance with Directive 94/33/EC for the protection of young people at work must be taken.

Take note of Directive 92/85/EC on the protection of pregnant and breastfeeding women at work

Registration, Evaluation, Authorization, and Restriction of Chemicals (REACH) Regulation (EC 1907/2006)

SVHC: Substances of Very High Concern for Authorisation:

This product does not contain candidate substances of very high concern at a concentration $\geq 0.1\%$ (Regulation (EC) No. 1907/2006 (REACH), Article 59)

EU-REACH (1907/2006) - Annex XVII - Substances subject to Restriction

This product contains one or more substance(s) subject to restriction (Regulation (EC) No. 1907/2006 (REACH), Annex XVII).

Chemical name	CAS No	Restricted substance per REACH Annex XVII
Diocetyl tinbis(acetylacetonate)	54068-28-9	20.

Substance subject to authorisation per REACH Annex XIV

This product does not contain substances subject to authorisation (Regulation (EC) No. 1907/2006 (REACH), Annex XIV)

Export Notification requirements

This product contains substances which are regulated pursuant to Regulation (EC) No. 649/2012 of the European parliament and of the council concerning the export and import of dangerous chemicals

Chemical name	European Export/Import Restrictions per (EC) 689/2008 - Annex Number
Diocetyl tinbis(acetylacetonate)	I.1

Ozone-depleting substances (ODS) regulation (EC) 1005/2009

Not applicable

Persistent Organic Pollutants

Not applicable

SAFETY DATA SHEET

OB1 HeatProtect Fire Resistant Hybrid 290ml White
Date 18.10.2024

Replaces: N/A
Ref:0641.0.BB/DL

National regulations

15.2. Chemical safety assessment

Chemical Safety Assessments have been carried out by the Reach registrants for substances registered at >10 tpa. No Chemical Safety Assessment has been carried out for this mixture

SECTION 16: Other information

Key or legend to abbreviations and acronyms used in the safety data sheet

Full text of H-Statements referred to under section 3

H226 - Flammable liquid and vapour
H302 - Harmful if swallowed
H315 - Causes skin irritation
H317 - May cause an allergic skin reaction
H318 - Causes serious eye damage
H332 - Harmful if inhaled
H335 - May cause respiratory irritation
H361f - Suspected of damaging fertility
H371 - May cause damage to organs
H400 - Very toxic to aquatic life
H410 - Very toxic to aquatic life with long lasting effects

Legend

TWA	TWA (time-weighted average)
STEL	STEL (Short Term Exposure Limit)
Ceiling	Ceiling Limit Value
*	Skin designation
SVHC	Substance(s) of Very High Concern
PBT	Persistent, Bioaccumulative, and Toxic (PBT) Chemicals
vPvB	Very Persistent and very Bioaccumulative (vPvB) Chemicals
STOT RE	Specific target organ toxicity - Repeated exposure
STOT SE	Specific target organ toxicity - Single exposure
EWC	European Waste Catalogue
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
IMDG	International Maritime Dangerous Goods (IMDG)
IATA	International Air Transport Association (IATA)
RID	Regulations concerning the International Transport of Dangerous Goods by Rail

Key literature references and sources for data

No information available

Prepared By Product Safety & Regulatory Affairs

Revision date 12-Apr-2022

Indication of changes

Revision note Not applicable.

Training Advice No information available

Further information No information available

This material safety data sheet complies with the requirements of Regulation (EC) No. 1907/2006

Disclaimer

SAFETY DATA SHEET

OB1 HeatProtect Fire Resistant Hybrid 290ml White
Date 18.10.2024

Replaces: N/A
Ref:0641.0.BB/DL

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet